

NBR-ACN elevator belting

NBR-ACN elevator belts are anti-static. The plies are polyester interwoven with Nylon layers. The belt is made out of NBR, (Nitrile Butadiene Rubber) with a high content of ACN (ACryl-Nitril).

The covers make it possible that the elevator bolt head will fit and countersunk perfectly. These belts are available in several breaking loads and thicknesses.

NBR (Nitrile Butadiene Rubber) with a high content of Acryl-Nitril covers are suitable for transporting products with a higher fat, oil and acid content. Often used in feedmill industry where hot oil products and molasses are processed.

Belts are cut and punched according to customers specifications.

Technical specifications	
NBR-ACN	
Production requirement acc.	DIN 22102 and 22104
Anti-static acc.	ISO 284
Pre stretched plies	Nylon / Polyester
Elongation	max. 1,5%
Covers	NBR-ACN 60 ± 5° Shore A
Breaking load covers	>= 12 N/mm
Abrasion	<= 200 mm ³
Density of covers	1,20 ± 0,3 gram/cm ³
Temperature resistance	-25 till +100 peak 120 °C
Swelling	Max 3% IRM903 oil, 20 °C, 21 days



NBR-ACN elevator belting						
Type of belt	Breaking load	Nr. of inserts	Covers	Thickness	Weight/m ²	Pulley Ø *
630/4	630 kg/cm ²	4	2+2 mm	9 mm	10,2 kg	500 mm
800/5	800 kg/cm ²	5	2+2 mm	10 mm	11,4 kg	630 mm
1000/5	1.000 kg/cm ²	5	2+2 mm	10 mm	12,6 kg	800 mm

* Recommended minimal pulley diameter (60 - 100% use of breaking load).